



## Advantage slideway 68 & 220

### Tenacious Fluid Lubricants

#### Description

**Advantage Slideway Lubricants** are specialty lubricants blended from highly refined mineral oils containing good lubricity, tackiness and extreme pressure additives.

#### Features & Benefits

**Advantage Slideway Lubricants** provide the following benefits:

- EP Agents Added - Minimises "Stick-Slip"
- Tacky Additive for Cohesion and Adhesion
- High Lubricity Factor
- High Film Strength Greater Shock Loads

#### Applications

**Advantage Slideway Lubricants** are designed for use on machine tools to eliminate or minimise "stick-slip" problems enabling finer adjustment of cutting tool feeds and improved surface finish of the work pieces.

#### Typical Physical and Chemical Properties

PRODUCT	68	220
Viscosity cSt @ 40°C (ASTM D445) @ 100°C (ASTM D445)	68 8.8	220 18.4
Pour Point °C	-21	-12
Density @ 15°C kg/L (ASTM D1298)	0.880	0.90
Flash Point °C	>200	>200

## Usage, Storage and Disposal

### Usage

Before using **Advantage Slideway Lubricants** please ensure that all safety requirements as set out on the Material Safety Data Sheet are observed and adhered to, if ever in doubt please contact your sales representative who will be happy to help by addressing any concerns or questions.

### Storage

Store according to instructions given on Material Safety Data Sheets.

### Disposal

Use an accredited Trade Waste Disposal Company, which complies with all the local environmental laws and regulations when disposing of any waste product.

### Health and Safety

Refer to Material Safety Data Sheet for the proper handling, use and disposal of this product. Product MSDS can be found at [www.mapal.com.au](http://www.mapal.com.au) for additional information contact MAPAL Australia on 1300 825 267.

## Product Shelf Life

Under normal conditions the recommended shelf life for **Advantage Slideway Lubricants** is a minimum of Twelve (12) months, unless otherwise specified.

## Availability and Shipping Classification

**Advantage Slideway Lubricants** are available in 205 litre drums. Other sizes may be available upon request, please contact your sales representative.

## Warranty

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied, since the use of our products is beyond our control. Statements concerning the use of Houghton products are not to be construed as recommending the infringement of any patent.

**Advantage Slideway Lubricants 68 & 220 are made in Australia**



MAPAL Australia Pty Ltd  
Unit 3/898, Humffray Street South,  
Mount Pleasant, VIC 3350  
Phone: 1300 825 267 | ABN 33 087 736 338  
[www.mapal.com.au](http://www.mapal.com.au) | [sales@mapal.com.au](mailto:sales@mapal.com.au)